

AS70 EXHAUST FANS

70 CFM/5.0 SONES @ 0.10" WG. -HVI CERTIFIED 120 Volts, 0.9 amps, 60 hz.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 95/8".

Blower Wheel

One piece polymeric wheel, 41/2" diameter, 1" wide, with 10 fins.

Motor

Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz., 0.9 amps.

Fan Housing

23 gauge galvanized metal housing, dimensions 73/8" x 71/2" x 33/4", double metal thickness mounting tabs.

Duct Collar

Plastic collar for 3" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area


For bathrooms up to 70 sq. ft. for other rooms up to 85 sq. ft.

Unit Mounting

Rated for ceilings insulated to R-40. Designed to mount in ceilings or walls with at least 4" of clearance. The housing will mount through drywall thickness up to $^{3}/_{4}$ ", with a rough-in opening of $^{73}/_{8}$ " x $^{71}/_{2}$ ".

• Single Pack Shipping Info

Box Dim: 10³/₄" x 10¹/₈" x 4³/₄" UPC: 0-8316227311-6 Shipping Weight: 4¹/₂ lbs.



CUL/HVI

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

	PERFORMANCE										
	Static Pressure (inches of wg.)								HVI Sones @ .1 SP	Fan Speed RPM	Power Watts
	0	0.1	0.125	0.5	0.2	0.25	0.3	0.4			
Air Flow - CFM	75	70	69	67	65	62	59	52	5.0	2175	50

PROJECT	Т							ARCHITECT			
LOCATIO	N							ENGINEER			
CONTRA	CONTRACTOR						SUBMITT	ED BY	DATE		
FAN	MODEL	CFM	IN	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT		
NUMBER	NUMBER	OI III	W.G.		WAITO	AIIII O	CONLO	411	& REMARKS		







QPTUSA International Corp 20851 Johnson Street Unit #105 Pembroke Pines, FL 33029 Phone: 305-883-9949 Email: info@qptusa.com