



## GULF-O-FLEX ALUMINUM TAPE

Is used for vapor sealing fiberglass duct board and sheets metal ducts. Specially designed for air-conditioning ducts. It's made from malleable aluminum foil with crossed linked acrylic.



### TECHNICAL PROPERTIES

Properties	Test Method	Unit	Specification
Color	Lab Test	Visually	Silver metallic
Backing	Lab test	n/a	Foil
Adhesive	ASTM D 3652	Micron	28 ± 5
Total Thickness	ASTM D 3652	Micron	45 ± 5
Peel Strength	ASTM D 3330	N/25mm	≥ 10
Tensile Strength	ASTM D 3759	N/25mm	≥ 20
Rolling Ball Tack	ASTM D 3121	mm	≤ 90

### TYPICAL USES

- General purpose holding, patching, sealing.
- Reflect heat & light away from sensitive area.
- Coupling and sealing pipe joints in ventilation, air condition and refrigeration systems.

### COLORS

AMI 100 Aluminum Foil Tape is available in silver metallic color only.

### SLIT ROLLS & JUMBO ROLLS

Width and length are available on request.

### PACKING

AMI 100 Aluminum Foil Tape is available in 16 and 24 standard rolls per carton. 1200 mm width x 1600 meters length jumbo roll.

### STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.



Distributed by:  
 QPTUSA International Corp  
 20851 Johnson Street - Unit#105  
 Pembroke Pines, FL 33029  
 Phone: 305-883-9949  
 Email: info@qptusa.com